

# Eastsign

## Reflective Banner/PVC

### Applications



- Digital and silk-screen printing
- Billboards
- Signage

### Features

- High reflectivity
- Good properties in tensile strength
- A Grade
- 3 years outdoor durability
- Easy welding
- Fire retardant and UV-proof
- Compatible with solvent ink

### Specifications

- Width: 1.35m/1.52m/1.80m/2.25m/2.70m/3.10m
- Thickness: 0.44mm – 0.60mm
- Temperature Range: 7°C – 24°C
- Scrim Denier: 200D x 500D



- High reflectivity
- Good properties in tensile strength
- A Grade



- Easy welding
- Fire retardant and UV-proof
- Compatible with solvent ink

	Specification	Size
Without Adhesive	DND, 200D x 500D, 450g±20, 0.45mm±0.02, for Digital Printing	Width: 1.35/ 1.52/ 1.80/ 2.25/ 2.70/ 3.10/ 3.15m Length: 50m
	SWS, 200D x 500D, 480g±20, 0.46mm±0.02, for Digital Printing	
	PYP, 200D x 500D, 510g±20, 0.50mm±0.02, for Digital Printing	
	DND, 200D x 300D, 360g±20, 0.40mm±0.02, for Digital Printing	
With Adhesive	DND, 340g±20, 0.42mm±0.02, for Digital Printing	Width: 1.05/ 1.24/ 1.35/ 1.52m; Length: 50m
	CPF, 440g±20, 0.45mm±0.02, for Digital Printing	Width: 1.22m; Length: 50m
	PVC, 430g±20, 0.47mm±0.02, for Digital Printing	Width: 1.22m; Length: 50m