

### Flatbed - FOT-H

#### For Materials in Pieces Only

- ★ Cut Piece Fabric
- ★ Carpet Towel
- ★ Flag Blanket
- ★ Rigid Sublimation Blanks

#### Features

- (A) Auto Timer
- (S) Dual Shuttle
- (P) Hydraulic Pressure: 0~10Mpa
- (T) 2~4 Groups of Temp control
- (B) Button Controlled Shuttle
- (F) Upper Aluminum Plate Heating



FOT-1224H



#### Specifications

Model	Workable Size (mm)	Workable Size (inch)	Rated Power (3 Phase 220V)	Max Amps (3 Phase 220V)	Rated Power (3 Phase 380V)	Max Amps (3 Phase 380V)	Dual Shuttle	Hydraulic Pressure	Auto Timer
FOT-1012H	900*1100	35.4"*43.3"	13KW	34A	16KW	24A	☑	☑	☑
FOT-1015H	900*1400	35.4"*55.1"	16KW	42A	19KW	29A	☑	☑	☑
FOT-1215H	1100*1400	43.3"*55.1"	20KW	52A	23KW	35A	☑	☑	☑
FOT-1224H	1100*2300	43.3"*90.5"	30KW	79A	39KW	59A	☑	☑	☑
FOT-1227H	1100*2600	43.3"*102.4"	34KW	89A	44KW	67A	☑	☑	☑
FOT-1527H	1400*2600	55.1"*102.4"	37KW	97A	48KW	73A	☑	☑	☑

★ All the parts are eligible for 15 months warranty under proper use. (Starting from the time of ETD)  
 ★ Specifications and external appearance are subject to change without prior notice