

## Application

- Suitable for automatic filling and packaging of powder and granule products.
- Different Package for Different Products.

## Sample



## Advantage

- PLC controlled, stable operation, flexible operation, strong adaptability, small footprint, low energy consumption and easy operation.
- Missing bag alarm function, manual-like bag correction, neater and more hygienic sealing.
- Independent PID temperature control, better compatible with various premade pouches.
- Human-machine interface with convenient and quick parameter setting.
- Fault alarm interface is clear and concise for easy troubleshooting at a glance.

## Specifications

NO.	Item	Description
1	Packaging Speed	20-60 bags/min
2	6-Station Operation Total	Bag picking, bag opening, detection, filling, sealing, bag discharging
3	Power	4.5KW
4	Bag Size	W 60-210mm / L 100-330mm
5	Power Supply	220V (Customizable)
6	Machine Weight	400KG (Main Unit)
7	Filling Volume	10-300ml
8	Air Consumption	0.7m <sup>3</sup> /min
9	Applicable Bags	Stand-up pouches, handle bags, zipper bags, 4-side seal bags, 3-side seal bags, paper bags
10	Machine Dimension	(w/o Auger) 1326X1320X1126mm (52.2X52X44.3inch)

### Eastsign Inc

3905 Hedgcoxe Rd, #250534, Plano, Dallas, TX75025, USA  
 US Cell / WhatsApp: +1-214-940-7888 Email: sales@eastsign.com



WhatsApp



www.eastsign.com

### Eastsign International Ltd

Rm 1818, 18/F., Shatin Galleria, 18-24 Shan Mei Street, Fotan, Shatin, N.T. Hong Kong  
 China Cell / WeChat: +86-138 2366 0955 Email: info@eastsign.com Fax: +852-21170099